



NOTES:

1. THIS STANDARD PROVIDES SOME, BUT NOT ALL REQUIRED SPECIFICATIONS. SEE THE **"SOLID WASTE PLAN GUIDE AND ENCLOSURE STANDARDS"** IN THE ENGINEERING PROCEDURES MANUAL FOR ADDITIONAL DETAILS.
2. A MINIMUM OF 32' VERTICAL AND 50' HORIZONTAL CLEARANCE OVER THE ENTIRE APPROACH TO AND FROM THE ENCLOSURE SHALL BE PROVIDED. NO ROOFS ALLOWED.
3. GATES SHALL BE SOLID METAL WITH CANE BOLTS/SLEEVES (SEE ST-34a) IN THE OPEN AND CLOSED POSITION. EACH GATE, WITH A MINIMUM TOTAL SPAN WIDTH OF 16' SHALL SWING OPEN A MIN OF 135° FROM CLOSED POSITION. HUNG GATES SHALL HAVE A 4" CLEARANCE OFF THE FINISHED PAD OR APRON AND SURROUNDING CURB.
4. THE TRASH ENCLOSURE PAD SHALL BE DESIGNED TO DRAIN TO A PERVIOUS SURFACE THROUGH INDIRECT SOIL INFILTRATION IN ACCORDANCE WITH THE CONTRA COSTA CLEAN WATER PROGRAM STORMWATER C.3 GUIDEBOOK (REFERENCE WEBSITE: <http://cccleanwater.org/construction/nd.php#Guidebook>). CONTACT THE CITY ENGINEER FOR ANY SPECIFIC STORMWATER CONCERNS.
5. THE EXTERIOR OF ENCLOSURE SHALL COMPLY WITH STANDARD CONDITIONS OF APPROVAL FOR COMMERCIAL AND INDUSTRIAL PROJECTS. NO ENCLOSURE SHALL BE INSTALLED BEHIND PARKING SPACES.
6. ONLY SOLID WASTE CONTAINERS ARE ALLOWED INSIDE THE ENCLOSURE. GREASE STORAGE BINS, SOILED RAG STORAGE, ETC. SHALL NEVER BE STORED IN THE ENCLOSURE. (Not To Scale)



PUBLIC WORKS DEPARTMENT



SOLID WASTE ENCLOSURE

B. Grewal

BALWINDER S. GREWAL CITY ENGINEER

DATE: DEC. 27, 2004

REVISED: JAN. 18, 2007

SHEET NO.

ST-34