


NOTES:

1. CONSTRUCT WEAKENED PLANE JOINTS ONE INCH DEEP AT 5'-0" ON CENTER.
2. CONSTRUCT EXPANSION JOINTS AT 20'-0" INTERVALS AND WHERE NEW CONCRETE JOINS EXISTING OR OTHER SURFACING.
3. ALL CONCRETE SHALL BE CLASS B, 2500 P.S.I. MINIMUM, WITH 1-1/2 LBS. FIBRILLATED POLYPROPELENE FIBERS PER CUBIC YARD.
4. BROOM-FINISH WALK AT RIGHT ANGLES.
5. ALL CONCRETE SHALL HAVE A MINIMUM 4" CUSHION OF CLASS 2 A.B. @ 95% RELATIVE COMPACTION (D1557-78) ON COMPACTED SUB-GRADE. THE USE OF RECYCLED A.B. SHALL NOT BE ALLOWED.
6. SUBGRADE SHALL BE SCARIFIED AND COMPACTED TO 95%.

(Not To Scale)



**ENGINEERING
DEPARTMENT**

CONCRETE WALKWAY DETAIL

B. Grewal
BALWINDER S. GREWAL CITY ENGINEER

DATE: OCT. 31, 2000
REVISED: AUG. 15, 2003

SHEET NO.
ST-17