


LEGEND:

- ① 1-1/2" SQUARE TUBULAR STEEL FRAME (TOP, BOTTOM & SIDE RAILS), WELDED ALL SIDES
- ② 3/4" ONE WAY, SELF-CLOSING HINGES, OPENING TOWARDS STREET
- ③ SELF-CLOSING BAR LATCH INCLUDING LOCK HASP, WELDED TO FRAME AND POST
- ④ 2-1/2" SQUARE TUBULAR POST, WELDED ALL SIDES
- ⑤ 5/8" TUBULAR STEEL PICKETS, WELDED ALL SIDES
- ⑥ CLASS A CONCRETE FOOTING, 2500 PSI MINIMUM

NOTES:

- 1. ALL WELDS SHALL BE GROUND SMOOTH.
- 2. ALL STEEL SHALL BE PAINTED WITH 1 COAT PRIMER, 2 COATS BLACK POLYURETHENE AND 2 COATS HIGH-GLOSS TNEMIC PAINT (OR APPROVED EQUAL).

(Not To Scale)



**ENGINEERING
DEPARTMENT**

IRON FENCE AND GATE

B. Grewal
BALWINDER S. GREWAL CITY ENGINEER

DATE: JULY 26, 2002
REVISED: JUNE 16, 2003

SHEET NO.
ST-19a